





1.01							
1.02					CPC35		
1.03			kg		3500		
1.04			mm		500		
1.05							
1.06							
2.01			H	mm	3000		
2.02			H1	mm	2120		
2.03			H2	mm	4217		
2.04			H3	mm	160		
2.05			H4	mm	2140		
2.06			H5	mm	135		
2.07			H6	mm	1050		
2.08			H9	mm	310		
2.09	/		(L/L')	mm	4166/2946		
2.10			L1	mm	1900		
2.11			L2	mm	484		
2.12			L3	mm	562		
2.13			W1	mm	1225		
2.14	/		W3/W2	mm	1000/970		
2.15		/	W5	mm	1060/250		
2.16			r	mm	2500		
2.17	/		/	deg.	10°/10°		
2.18			(L4xWxT)	mm	1220x 125x 50		
2.19			Ast	mm	3134		
3.01	/		/	km/h	22/23		
3.02				%	22		
3.03	/		/	kN	19/15		
3.04	/		/	mm/s	400/420		
3.05	/		/	mm/s	450/460		
4.01				kg	4800		
5.01	X=	/			2X/2		
5.02	/						
5.03	/				28x 9-15-14PR/6.5-10-10PR		
5.04					-		
5.05					-		
6.01	/			V/Ah	12/80		
6.02	/	/			V29.50V/42 493VP		
6.03	/			kW/rpm	36.8/2500		
6.04	/			Nm/rpm	170/1800		
6.05	-	x	/	/L	4-93x 105/2.85		
6.06				L	70		
6.07							
6.08					2- 2		
M300	3000	3500	500mm KG	36.8/2500	2120	4800	10/10